


Flex Strip Range




IP Rating	20 or 65 (Nano)
Dimensions (mm)	Refer to Line Drawing
Mounting	Surface Mount (Flat-Bar) Built-in to extrusion Profile options below

Product Specifications

LED Driver	Required (24V)
Light Source	LED
Available CCT	3000K, 4000K, Other
CRI	> 80, Other
Lifetime	Determined by thermal management properties
Application Temperature	Ta < 35°C
Colour Consistency	Mac Adams <3 SDCM
3 Year warranty	Subject to Lightnet T's and C's




*Cutting Increments 50mm, Full roll 5m




LSS5035


Available Profiles




LCF 1818




LCR 1616




LS1715




LSS5050




LCQ 1616



LR1715



LR3628



LR6535

CCT	CRI	Wattage	Voltage	Lumens/m	Efficacy
(K)	(Ra)	(W)	(V)	(lm/m)	(lm/W)
3000	80	9.6	24	920	96
3000	80	14.4	24	1 454	101
4000	80	9.6	24	1 040	108
4000	80	14.4	24	1 499	104

*Cutting Increments 50mm, Full roll 5m

Tolerance range of optical and electrical data is ± 10%.

Wattage does not include power consumption of driver (Additional 8-15%).

Please note: Data may be rounded up/down for illustrative purposes. We reserve the right to amend or change details without prior notification. E&OE