

Auge Bulkhead



Application:

As an IP65 Luminaire, The auge is well-suited for perimeter lighting around residential and commercial buildings, staircase and outdoor canopies, serving as illumination for pedestrians. Operating temperatures $\leq 35^{\circ}\text{C}$.



Retail



Public Facilities



Hospitality



Commercial



Residential



1.14 Kg



Refer to Line drawing




IP65




IK08



Die Cast Aluminium



Auge Bulkhead



Top Eyelid Auge Bulkhead

Product Overview

High quality LED:

CRI ≥ 80 as a standard
4000K as a standard

Integrated LED driver:

220 – 240V input (50/60 Hz)
Ripple and flicker free ($\leq 3\%$)
Power factor ≥ 0.90
Surge protection: 3.75 KVA
DALI available on request

PC Diffuser:

UV stabilized

Housing:

Die Cast aluminium (LM2)
Black as a standard
Other colours available on request
Stainless steel Heli-Coils

Standard Warranty of luminaire is 5 years subjected to Lightnet T's and C's

Nominal Wattage	Nominal Lumens	System Wattage	System Lumens	Code
11 W	1 875 lm	13 W	1 180 lm	34022000LD840/11/350
16 W	2 675 lm	18 W	1 685 lm	34022000LD840/16/500

Values based on Auge Bulkhead

Produced/Assembled in South Africa

5-year warranty

Tolerance range of optical and electrical data is $\pm 10\%$.

Optical and electrical data may increase or decrease with a change of specifications and availability of components.

Please note: Data may be rounded up/down for illustrative purposes. We reserve the right to amend or change details without prior notification. E&OE REV23042024.