

24V Strip Light 9.6W/m (IP20)



Product Overview

High quality LED:

Input Voltage: DC24V
CCT: 3000K / 3500K / 4000K / 6000K
CRI: 80
Max Power: 9.6 W/m
Power range: 7.5 to 9.6 W/m
Typical power: 8.4 W(1m) / 33.6W (5m)
Rated current: 0.35A (1m) / 1.4A (5m)
On/off Cycles: > 10 000 (Test times)

Mechanical Parameters

IP20
Width: 8mm
Max Length: 5000mm
Cutting increments: 50mm / 6 LED's
LED Pitch: 8.33mm
Min Bend diameter: Ø 60mm
Adhesive: High thermal 3M

Additional

24V Control Gear 75W
24V Control Gear 150W
Mini Profiles

Warranty: 3 year (strip)
5 year (control gear)

CCT (mA)	CRI (Ra)	Ingress protection (IP)	Wattage (W/m)	Lumens (lm/m)	Code (K)
3000K	80	20	9.6	960	4CO/LDC/9.6/3K
3500K	80	20	9.6	955	4CO/LDC/9.6/3.5K
4000K	80	20	9.6	1 040	4CO/LDC/9.6/4K
6000K	80	20	9.6	1 000	4CO/LDC/9.6/6K



Retail



Public
Facilities



Residential



Hospitality



Commercial

Control Gear (IP20)

Max Output (W)	Output Voltage (V)	Power factor λ	Efficiency (Full Load) (%)	Ambient temp. (°C)	Isolation	Dimensions (mm)	Code
75	24	0.95	89	-20 ~ +50	SELV	184x61x32	1AC/Q8H-24V-75W/CN
150	24	0.95	91	-20 ~ +45	SELV	210x67x34	1AC/Q8H-24V-150W/CN

Tolerance of output data can vary up to 15%

Output data is tested according to IES TM-30-15

Please note: Data may be rounded up/down for illustrative purposes. We reserve the right to amend or change details without prior notification. E&OE